

## QUAD BAND GSM MAGNETIC MOUNT ANTENNA

2.5 TO 5 METER CABLE



QUAD BAND GSM MAGNETIC MOUNT  
ANTENNA with 2.5 TO 5 METER CABLE

### MAIN SPECIFICATIONS GSM 850/900/1800/1900

#### GSM 1800 (1710-1880 MHZ)

|              |        |
|--------------|--------|
| Gain         | <1 dBi |
| VSWR         | <2     |
| Impedance    | 50 OHM |
| Polarization | linear |

#### GSM 1900 (1850-1990 MHZ)

|              |        |
|--------------|--------|
| Gain         | <0 dBi |
| VSWR         | <2,5   |
| Impedance    | 50 OHM |
| Polarization | linear |

### APPLICATIONS

- Automotive
- Telemetry

### MAIN FEATURES

- Flexible enclosure
- Easy to install.
- IP67 (on standard version)
- RoHS compliant
- Good efficiency

### MAIN SPECIFICATIONS GSM

#### 850/900/1800/1900

#### GSM 850 (824-894 MHZ)

|              |        |
|--------------|--------|
| Gain         | <0 dBi |
| VSWR         | <2,5   |
| Impedance    | 50 OHM |
| Polarization | linear |

#### GSM 900 (890-960 MHZ)

|              |        |
|--------------|--------|
| Gain         | <1 dBi |
| VSWR         | <2     |
| Impedance    | 50 OHM |
| Polarization | linear |

### DIMENSIONS & AL.

|              |   |
|--------------|---|
| Dimensions   | 04x35 mm                                      |
| Cable        | all coaxial cables Z0 50<br>OHM diam < 3,6 mm |
| Cable length | 2.5 or 5 meter                                |
| Connector    | FME JACK                                      |