

Coil voltage 24 V DC; AC/DC

OUTPUT 250 V AC / 6 A – 1 CHANGEOVER CONTACT

APPROVALS : CSA, UL IN PREPARATION

AgSnO ₂	AgSnO ₂ + Au (5 μ)
80.010.4502.0	80.010.4502.1
80.010.4522.0	80.010.4522.1
24 V DC	24 V AC / DC
28.8 V DC	26.4 V AC / DC
18.2 V DC	19.2 V AC / DC
9.4 mA	12 mA
0.23 W	0.3 V A
(0.7 ... 2.2)U _N	(0.85 ... 1.1) U _N
20 Modules	
LED green	
AgSnO ₂	AgSnO ₂ + Au (5 μ)
400 V AC	
250 V AC	
6 A AC / DC	
1500 V A / 150 W	
30 A (0.5 sec.)	
7 ms / 11 ms	
20 Hz (without load); 0.1 Hz (at full load)	
AgSnO ₂	AgSnO ₂ + Au (5 μ)
12 V AC / DC	5 V AC / DC
10 mA AC / DC	2 mA AC / DC
500 mW	50 mW
1 x 10'	
6 x 10'	
250 V	
4 kV _{eff.}	
III (in accordance with HD 625.1S1)	
2 (in accordance with HD 625.1S1)	
0 °C...+50 °C	
-40 °C...+55 °C	
IP 20 / TS35	
0.14 mm ² - 1.5 mm ² / 0.5 mm ² - 2.5 mm ²	



Relay type	Part No.
80.063.4032.0	80.063.4032.1 (+ Au (5 μ))
12 or 24 V DC	80.063.4001.1
12 or 24 V DC	80.063.4021.1
60 V DC	80.063.4023.1
60 V DC	80.063.4025.1
60 V DC	80.063.4026.1
IP SF38	80.063.4009.1
KB SF38	80.063.4029.1
BZ SF38	80.063.4029.3
BM SF38	80.063.4129.3